


Features

- 700 Watts Peak Pulse Power per Line ($t_p=8/20\mu s$)
- Small Body Outline Dimensions
- Protects one I/O or power line
- Working Voltage: 3.3V
- Low Leakage Current

IEC COMPATIBILITY (EN61000-4)

- IEC 61000-4-2 (ESD) $\pm 30kV$ (air), $\pm 30kV$ (contact)
- IEC 61000-4-4 (EFT) 40A (5/50ns)
- IEC 61000-4-5 (Lightning) 70A (8/20 μs)




Mechanical Characteristics

- DFN1006-2L package
- Marking : Marking Code
- Packaging : Tape and Reel per EIA 481
- RoHS Compliant & HF
- Device meets MSL1 requirement

Applications

- Cellular Handsets & Accessories
- Personal Digital Assistants (PDAs)
- Notebooks & Handhelds
- Portable Instrumentation
- Digital Cameras


Schematic & PIN Configuration



| Absolute Maximum Rating | | | |
|--|-----------|--------------|-------|
| Rating | Symbol | Value | Units |
| Peak Pulse Power ($t_p = 8/20\mu s$) | P_{PP} | 700 | Watts |
| Peak Pulse Current ($t_p = 8/20\mu s$) | I_{PP} | 70 | A |
| Operating Temperature | T_J | -55 to + 125 | °C |
| Storage Temperature | T_{STG} | -55 to +150 | °C |

Electrical Parameters

| Symbol | Parameter |
|-----------|-------------------------------------|
| I_{PP} | Reverse Stand-Off Voltage |
| V_C | Clamping Voltage @ I_{PP} |
| V_{RWM} | Reverse Stand-Off Voltage |
| I_R | Reverse Leakage Current @ V_{RWM} |
| V_{BR} | Breakdown Voltage @ I_T |
| I_T | Test Current |



Electrical Characteristics(T=25°C unless otherwise noted)

| WS03DPMF-BH | | | | | | |
|-----------------------------------|-----------|---------------------------------------|---------|---------|---------|----------|
| Parameter | Symbol | Conditions | Minimum | Typical | Maximum | Units |
| Reverse Stand-Off Voltage | V_{RWM} | | | | 3.3 | V |
| Reverse Breakdown Voltage | V_{BR} | $I_T=1mA$ | 3.7 | | | V |
| Reverse Leakage Current | I_R | $V_{RWM}=3.3V$ | | | 200 | nA |
| Clamping Voltage | V_C | $I_{PP}=70A, t_p=8/20\mu s$ | | 8 | 10 | V |
| Dynamic Resistance ^{1,2} | R_{DYN} | TLP=0.2/100ns | | 0.08 | | Ω |
| ESD Clamping Voltage ¹ | V_C | $I_{PP} = 4A, t_p = 0.2/100ns$ (TLP) | | 4.6 | | V |
| ESD Clamping Voltage ¹ | V_C | $I_{PP} = 16A, t_p = 0.2/100ns$ (TLP) | | 5.6 | | V |
| Junction Capacitance | C_j | $V_R=0V, f=1MHz$ | | | 240 | pF |

Notes : 1、 TLP Setting : $t_p=100ns, t_r=0.2ns, I_{TLP}$ and V_{TLP} sample window: $t_1=70ns$ to $t_2=90ns$.
 2、 Dynamic resistance calculated from $I_{PP}=4A$ to $I_{PP}=16A$ using "Best Fit".

Typical Characteristics

Figure 1: Peak Pulse Power Vs Pulse Time




Figure 2: Power Derating Curve




Figure 3: Clamping Voltage vs. Peak Pulse Current




Figure 4: Normalized Junction Capacitance vs. Reverse Voltage




Figure 5: TLP Positive I-V Curve






Figure 6: TLP Negative I-V Curve




Soldering Parameters

| Reflow Condition | | Pb – Free assembly |
|--|----------------------------------|--------------------|
| Pre Heat | Temperature Min ($T_{s(min)}$) | 150°C |
| | Temperature Max ($T_{s(max)}$) | 200°C |
| | Time (min to max) (t_s) | 60 – 190 secs |
| Average ramp up rate (Liquidus Temp) (T_L) to peak | | 5°C/second max |
| $T_{s(max)}$ to T_L —Ramp-up Rate | | 5°C/second max |
| Reflow | Temperature (T_L) (Liquidus) | 217°C |
| | Temperature (t_L) | 60 – 150 seconds |
| Peak Temperature (T_P) | | 260+0/-5 °C |
| Time within actual peak Temperature (t_p) | | 20 – 40 seconds |
| Ramp-down Rate | | 5°C/second max |
| Time 25°C to peak Temperature (T_P) | | 8 minutes Max. |
| Do not exceed | | 280°C |




Tape And Reel Information


Reel Dimensions



Tape Dimensions



Quadrant Assignments For PIN1 Orientation In Tape



| | | |
|----|---|--------|
| RD | Reel Dimensions | 7 inch |
| W | Overall width of the carrier tape | 8 mm |
| P1 | Pitch between successive cavity centers | 2mm |

Outline Drawing –DFN1006-2L

PACKAGE OUTLINE

Bottom View Top View

Side View

DFN1006-2L

| SYMBOL | MILLIMETERS | | |
|--------|-------------|-------|-------|
| | NOM | MIN | MAX |
| A | -- | 0.35 | 0.400 |
| A1 | -- | -- | 0.050 |
| D | 1.020 | 0.990 | 1.050 |
| E | 0.620 | 0.590 | 0.650 |
| b | 0.480 | 0.430 | 0.530 |
| L | 0.220 | 0.170 | 0.270 |
| h | 0.125 | 0.075 | 0.175 |
| L1 | 0.075REF | | |
| L2 | 0.070REF | | |
| e | 0.650REF | | |

Land Pattern

Marking Codes

| Part Number | Marking Code |
|-------------|---|
| WS03DPMF-BH | <div style="display: flex; align-items: center; justify-content: center;"> 1 <div style="border: 1px solid black; padding: 10px; font-size: 2em; font-weight: bold;">EE</div> 2 </div> |

Package Information

Qty: 10k/Reel

CONTACT INFORMATION

No.1001, Shiwan (7) Road, Pudong District, Shanghai, P.R.China.201207

Tel: 86-21-68969993 Fax: 86-21-50757680 Email: market@way-on.com

WAYON website: <http://www.way-on.com>

For additional information, please contact your local Sales Representative.

WAYON ® is registered trademark of WAYON Corporation.

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.